

DECLARATION OF PERFORMANCE

No. CPR_01

1. Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption Eb ≤ 0,5 %**
2. Intended uses: **For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer: **Ceramiche Keope, S.S. 467 n° 21 42013 Casalgrande (RE) ITALY**
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

| Essential characteristics | Performance | Harmonised technical specification |
|---|----------------------|------------------------------------|
| Reaction to fire | A1 _{FL} /A1 | EN 14411:2012 |
| Release of dangerous substance (only for GL ceramic tiles): | | |
| - Cadmium | npd | |
| - Lead | npd | |
| Breaking strength (thickness ≥ 7,5) | ≥ 1300 N | |
| Breaking strength (thickness < 7,5) | ≥ 700 N | |
| Slipperiness | See table attached | |
| Tactility | npd | |
| Bond strength/adhesion | npd | |
| Thermal shock resistance | Pass | |
| Durability for: | | |
| - internal use: | Pass | |
| - external use: freeze-thaw resistance | Pass | |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Davide Mussini – Managing Director

.....
 Name and function



Casalgrande (RE) Italy, 20/05/2021

.....
 Place, date

.....
 Signature

Table - Slipperiness rev. 20/05/2021

| | DIN 51130 (DE) | BCRA D.M. 236/1989 (ITA) |
|--------------|----------------|--------------------------|
| LINEO WHITE | R9 | > 0,40 |
| LINEO HONEY | | |
| LINEO SAND | | |
| LINEO BROWN | | |
| LINEO WALNUT | | |
| LINEO ROW | | |
| LINEO HONEY | R11 | > 0,40 |
| LINEO SAND | | |
| LINEO WALNUT | | |