



DECLARATION OF PERFORMANCE

No. FLORIM 001

(EN) - Rev. 1

1. Unique identification code of the product type
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$
2. Intended use(s)
For internal and external walls and floorings
3. Name or registered trade mark, and contact address of the manufacturer
**FLORIM CERAMICHE S.p.A. SB,
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)
System 4
5. Name and identification number of notified laboratory, if relevant – **Not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411:2012
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued in accordance with regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

This declaration is available on the website <https://www.florim.com/en/declarations-of-performance-ce/>.

Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 29/04/2021

.....
Place and date of issue


.....
Signature

Florim Ceramiche S.p.A. SB a socio unico

via Canaletto 24, Fiorano Modenese (MO) 41042 – Italia | T +39 0536 840111 | F +39 0536 844750 | florim.com

Capitale sociale euro 50.000.000 i.v. | Reg. Imprese C.C.I.A.A. di Modena | C.F. e P.IVA IT 01265320364 | Codice SDI MZO2A0U



Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata
Bijlage bij de prestatieverklaring
Navezanost na izjave o lastnostih
Aneks Izjave o svojstvima
No. FLORIM 001

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutschsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogsabály szerint szükséges)
Tabel - Antislipwaarde (indien door de wetgever vereist)
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)
Rev. 14 del/of/de/vom/de/a 19.10.2021

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

FLOOR GRES


Serie / Series / Kolekcja / Serija	CEN/TS 16165:2012 Annex B α_{SHOD}	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
AIRTECH high-glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
AIRTECH naturale	N.P.D.	N.P.D.	R9	N.P.D.
AIRTECH strutturato	N.P.D.	>0,4	R11	N.P.D.
B&W Marble glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
B&W Marble matte	N.P.D.	>0,4	R9	N.P.D.
BUILDTECH 2.0 levigato	N.P.D.	N.P.D.	N.P.D.	N.P.D.
BUILDTECH 2.0 naturale	N.P.D.	>0,4	R10	N.P.D.
BUILDTECH 2.0 R+PTV	N.P.D.	>0,4	R10	N.P.D.
BUILDTECH 2.0 soft	N.P.D.	N.P.D.	R9	N.P.D.
BUILDTECH 2.0 strutturato	N.P.D.	>0,4	R11	N.P.D.
EARTHTECH comfort	N.P.D.	>0,4	R10	N.P.D.
EARTHTECH glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
EARTHTECH strutturato	N.P.D.	>0,4	R11	N.P.D.
EARTHTECH strutturato 20 mm	N.P.D.	>0,4	R11	N.P.D.
FLOORTECH naturale	N.P.D.	>0,4	R10	Classe 2
FLOORTECH soft	N.P.D.	>0,4	R9	N.P.D.
FLOORTECH strutturato	N.P.D.	>0,4	R11	N.P.D.
FLOWTECH naturale	N.P.D.	N.P.D.	R9	N.P.D.
GREENTECH naturale	N.P.D.	>0,4	R10	N.P.D.
GREENTECH strutturato	N.P.D.	>0,4	R11	N.P.D.
INDUSTRIAL bocciardato	N.P.D.	>0,4	R11	Classe 3
INDUSTRIAL bocciardato 20 mm	N.P.D.	>0,4	R11	N.P.D.
INDUSTRIAL naturale	N.P.D.	>0,4	R10	Classe 1
INDUSTRIAL soft	N.P.D.	N.P.D.	R9	N.P.D.
PISCINE MOD 2/25	N.P.D.	>0,4	R11	N.P.D.
RAWTECH naturale	N.P.D.	>0,4	R10	Classe 2
RAWTECH strutturato	N.P.D.	>0,4	R11	N.P.D.



STONTECH 4.0 cannetè	N.P.D.	N.P.D.	R9	N.P.D.
STONTECH 4.0 high glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
STONTECH 4.0 naturale	N.P.D.	N.P.D.	R9	N.P.D.
STONTECH 4.0 R+PTV	N.P.D.	>0,4	R10	N.P.D.
STONTECH 4.0 strutturato	N.P.D.	>0,4	R11	N.P.D.
TECH/2	N.P.D.	>0,4	R12	N.P.D.
WALKS 1.0 naturale	N.P.D.	>0,4	R11	Classe 3
WALKS 1.0 naturale 20 mm	N.P.D.	>0,4	R11	N.P.D.
WALKS 1.0 soft	N.P.D.	N.P.D.	R9	N.P.D.

CE MARKING

Fine porcelain stoneware
Glazed porcelain stoneware
Coloured body porcelain stoneware

	
FLORIM CERAMICHE S.p.A. SB, Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
05 FLORIM 001	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 1300 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
https://www.florim.com/en/complete-ce-marking/	