

## DECLARATION OF PERFORMANCE

No. CPR\_01

1. Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption Eb ≤ 0,5 %**
2. Intended uses: **For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer: **Ceramiche Keope, S.S. 467 n° 21 42013 Casalgrande (RE) ITALY**
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	EN 14411:2012
Release of dangerous substance (only for GL ceramic tiles):		
- Cadmium	npd	
- Lead	npd	
Breaking strength (thickness ≥ 7,5)	≥ 1300 N	
Breaking strength (thickness < 7,5)	≥ 700 N	
Slipperiness	See table attached	
Tactility	npd	
Bond strength/adhesion	npd	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

*Davide Mussini – Managing Director*

.....  
 Name and function



Casalgrande (RE) Italy, 10/10/2017

.....  
 Place, date

.....  
 Signature

**Table - Slipperiness rev. 10/10/2017**

E.LUX	DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)
E.L. CALACATTA LAP.	NPD	NPD
E.L. EMPERADOR LAP.		
E.L. CREMA BEIGE LAP.		
E.L. SILVER GREY LAP.		
E.L. PORT LAURENT LAP.		
E.L. LINCOLN LAP.		
E.L. GRIGIO IMPERIALE LAP.		
E.L. CALACATTA GOLD LAP.		
E.L. CALACATTA R9		
E.L. EMPERADOR R9		
E.L. CREMA BEIGE R9		
E.L. SILVER GREY R9		
E.L. PORT LAURENT R9		
E.L. LINCOLN R9		
E.L. GRIGIO IMPERIALE R9		
E.L. CALACATTA GOLD R9		