



## DECLARATION OF PERFORMANCE

No. FLORIM 003

(EN) - Rev. 1

1. Unique identification code of the product type  
**Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5 \%$**
2. Intended use(s)  
**For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer  
**FLORIM CERAMICHE S.p.A. SB,  
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**
5. Name and identification number of notified laboratory, if relevant – **Not applicable**  
Task(s) carried out  
AVCP system  
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub> /A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411:2012
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 700 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued in accordance with regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

This declaration is available on the website <https://www.florim.com/en/declarations-of-performance-ce/>.

Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....  
Name and function

Fiorano Modenese, 01/09/2021

.....  
Place and date of issue

  
.....  
Signature



Allegato alla Dichiarazione di Prestazione  
Attachment to Declaration of Performance  
Annexe à la déclaration de performance  
Anhang der Leistungserklärung  
Anexo a la Declaración de Performance  
Załącznik do deklaracji właściwości użytkowych  
A Teljesítmény Nyilatkozat kiegészítő táblázata  
Bijlage bij de prestatieverklaring  
Navezanost na izjave o lastnostih  
Aneks Izjave o svojstvima  
No. FLORIM 003

Tabella - Scivolosità (dove richiesto dalla legislazione)  
Table - Slipperiness (where required by regulation)  
Table - Glissement (si requis par la loi)  
Tabelle - Rutschsicherheit (wo erforderlich durch die Gesetzgebung)  
Tabla - Deslizamiento (donde sea requerido por ley)  
Tabela - Poslizgowosc (gdzie wymagane przez prawo)  
Táblázat - Csúszásmentesség (ahol jogsabály szerint szükséges)  
Tabel - Antislipwaarde (indien door de wetgever vereist)  
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)  
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)  
Rev. 11 del/of/de/vom/de/a 19.10.2021


Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

## FLOOR GRES

Serie / Series / Kolekcja / Serija	CEN/TS 16165:2012 Annex B $\alpha_{SHOD}$	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
B&W Marble Magnum glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
B&W Marble Magnum matte	N.P.D.	>0,4	R9	N.P.D.
BUILDTECH 2.0 Magnum naturale	N.P.D.	>0,4	R9	N.P.D.
BUILDTECH 2.0 Magnum R+PTV	N.P.D.	>0,4	R10	N.P.D.
BUILDTECH Magnum levigato	N.P.D.	N.P.D.	N.P.D.	N.P.D.
EARTHTECH MAGNUM comfort	N.P.D.	>0,4	R10	N.P.D.
FLOWTECH Magnum naturale	N.P.D.	N.P.D.	R9	N.P.D.
FLOWTECH Magnum R+PTV	N.P.D.	>0,4	R10	N.P.D.
INDUSTRIAL Magnum naturale	N.P.D.	N.P.D.	R9	N.P.D.
INDUSTRIAL Magnum R+PTV	N.P.D.	>0,4	R10	N.P.D.
PISCINE GRIP SM	N.P.D.	N.P.D.	N.P.D.	N.P.D.
PISCINE LISCIO SM	N.P.D.	N.P.D.	N.P.D.	N.P.D.
RAWTECH MAGNUM	N.P.D.	>0,4	R9	N.P.D.
STONTECH 4.0 magnum high-glossy	N.P.D.	N.P.D.	N.P.D.	N.P.D.
STONTECH 4.0 magnum matte	N.P.D.	>0,4	N.P.D.	N.P.D.
STONTECH 4.0 magnum R+PTV	N.P.D.	>0,4	R10	N.P.D.

# CE MARKING

## Fine porcelain stoneware MAGNUM

	
<b>FLORIM CERAMICHE S.p.A. SB,</b> <b>Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia</b>	
09 FLORIM 003	
<b>EN 14411:2012</b> Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$ , for internal and external walls and floorings	
<b>Reaction to fire</b>	A1 <sub>FL</sub> /A1
<b>Release of dangerous substances, for:</b>	
- Cadmium	NPD
- Lead	NPD
<b>Breaking strength</b>	> 700 N
<b>Slipperiness, as:</b>	See table attached
<b>Tactility</b>	NPD
<b>Bond strength/adhesion, for:</b>	
Cementitious adhesive, type C2	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability, for:</b>	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
<a href="https://www.florim.com/en/complete-ce-marking/">https://www.florim.com/en/complete-ce-marking/</a>	