



DECLARATION OF PERFORMANCE

No. FLORIM 001

1. Unique identification code of the product type
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$
2. Intended use(s)
For internal and external walls and floorings
3. Name or registered trade mark, and contact address of the manufacturer
**FLORIM CERAMICHE S.p.A. SB,
Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia**
4. System(s) of assessment and verification of constancy of performance (AVCP)
System 4
5. Name and identification number of notified laboratory, if relevant – **Not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FJ} /A1	Based on the decision 96/603/CE and its changes
Release of dangerous substance, for:		EN 14411:2012
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued in accordance with regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3. This declaration is available on the website <https://www.florim.com/en/declarations-of-performance-ce/>. Signed for and on behalf of the manufacturer by:

Bruni Donato – Amministratore Delegato

.....
Name and function

Fiorano Modenese, 01/03/2021

.....
Place and date of issue


.....
Signature



**Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata
Bijlage bij de prestatieverklaring
Navezanost na izjave o lastnostih
Aneks Izjave o svojstvima
No. FLORIM 001**

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutschsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogsabály szerint szükséges)
Tabel - Antislipwaarde (indien door de wetgever vereist)
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)
Rev. 16 del/of/de/vom/de/a 10.06.2021

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka


CASA DOLCE CASA

Serie / Series / Kolekcja / Serija	CEN/TS 16'165:2012 Annex B α_{SHOD}	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ARTWORK glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
ARTWORK matte	N.P.D.	N.P.D.	R9	N.P.D.
ARTWORK R+PTV	N.P.D.	>0,4	R10	N.P.D.
FLAGSTONE 2.0 glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
FLAGSTONE 2.0 matte	N.P.D.	N.P.D.	R10	N.P.D.
FLAGSTONE 2.0 strutturato	N.P.D.	>0,4	R11	N.P.D.
ICON OUTDOOR	N.P.D.	>0,4	R11	N.P.D.
MOTION	N.P.D.	N.P.D.	R9	N.P.D.
MOTION strutturato	N.P.D.	>0,4	R11	Classe 3
NEUTRA 6.0 tinte unite	N.P.D.	N.P.D.	N.P.D.	N.P.D.
NEUTRA 6.0 tinte unite grip	N.P.D.	>0,4	R11	N.P.D.
ONYX & MORE GLOSSY	N.P.D.	>0,4	N.P.D.	N.P.D.
ONYX & MORE SATIN	N.P.D.	>0,4	N.P.D.	N.P.D.
ONYX & MORE STRUTTURATO	N.P.D.	>0,4	R10	Classe 1
PIETRE 3 naturale	N.P.D.	>0,4	R10	N.P.D.
PIETRE 3 strutturato	N.P.D.	>0,4	R11	N.P.D.
PIETRE 3 strutturato 20 mm	N.P.D.	>0,4	R11	N.P.D.
SENSI Dust Fossil matte	N.P.D.	>0,4	R9	N.P.D.
SENSI Fossil R+PTV	N.P.D.	>0,4	R10	Classe 2
SENSI Lithos matte	N.P.D.	>0,4	R10	N.P.D.
SENSI Sand matte	N.P.D.	>0,4	R11	N.P.D.
STONES & MORE 2.0 matte (stone burl white-stone burl gray)	N.P.D.	>0,4	R10	N.P.D.
STONES & MORE 2.0 glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
STONES & MORE 2.0 matte (Stone zecevo - Arabascato White - Amani Bronze - Stone sahara Noir)	N.P.D.	>0,4	R9	N.P.D.

STONES & MORE 2.0 smooth	N.P.D.	>0,4	R9	N.P.D.
STUDIOS OF CASAMOOD grip	N.P.D.	>0,4	R11	N.P.D.
STUDIOS OF CASAMOOD grip 20 mm	N.P.D.	>0,4	R11	N.P.D.
STUDIOS OF CASAMOOD matte	N.P.D.	N.P.D.	R10	N.P.D.
URBAN STYLE	N.P.D.	>0,4	R10	N.P.D.
URBAN STYLE STRUTTURATO	N.P.D.	>0,4	R11	N.P.D.
URBAN STYLE STRUTTURATO 20 MM	N.P.D.	>0,4	R11	N.P.D.
WOODEN TILE WALNUT naturale	N.P.D.	>0,4	R9	Classe 1
WOODEN TILE naturale	N.P.D.	>0,4	R10	N.P.D.
WOODEN TILE strutturato	N.P.D.	>0,4	R11	Classe 2

CE MARKING

Fine porcelain stoneware
Glazed porcelain stoneware
Coloured body porcelain stoneware

	
FLORIM CERAMICHE S.p.A. SB, Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
05 FLORIM 001	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 1300 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass
https://www.florim.com/en/complete-ce-marking/	